

According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

LA LMM-14 AerosolGSLA_LMM-14 Black Aerosol Spray CanProduct specificationRS_FP_603542Revision Date04/19/2018Version1.13Print Date06/18/2018Material number1407083PagePage 1 of 17

SECTION 1. IDENTIFICATION

Product name : LA LMM-14 Aerosol

GSLA_LMM-14 Black Aerosol Spray Can

Material number : 1407083

Manufacturer or supplier's details

Company name of supplier : RINSYUNDOU Co.,Ltd

Address : SUNMAX Building4-47 Nakagawara, Gifu City, GIFU-Pref.

Postal Code 502-0013

Telephone : 058-294-7333

Emergency telephone number

In-Country Number : 058-294-7333 CHEMTREC Global Number : 0081+58294-7333

Recommended use of the chemical and restrictions on use

Recommended use : Consult the technical guidelines for the use of this substance/mixture.

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable aerosols : Category 1

Eye irritation : Category 2A

Carcinogenicity : Category 1A

Gases under pressure : Category 1

GHS Label element

Hazard pictograms







Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may

explode if heated.

H319 Causes serious eye irritation.



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

I A I MM 14 A 1			CCLA	I MM 44 Dlook A am	and Surrey Care
LA LMM-14 Aerosol Product specification	RS_FP_603	5 <i>1</i> 2	Revision	LMM-14 Black Aero	04/19/2018
Version	1.13	342	Print Da		06/18/2018
Material number	1407083		Page	ii.G	Page 2 of 17
	1407000		i ago		- ago 2 or 17
		H350		May cause cancer.	
Precautionary staten	nents :	Prevention:			
•		P201			
				Obtain special instru	uctions before use.
		P202		Do not handle until	all safety
				precautions have be	een read and
				understood.	
		P210		Keep away from he flames/hot surfaces	
		P211		Do not spray on an	_
		1 2 1 1		other ignition source	
		P251		Pressurized contain	
				or burn, even after	
		P264		Wash skin thorough	
		P280		Wear protective glo	
		00		clothing/ eye protect	
				protection.	
		Response:		•	
		•	+ P338	IF IN EYES: Rinse	cautiously with
				water for several mi	•
				contact lenses, if pr	resent and easy to
				do. Continue rinsing	
		P308 + P313		IF exposed or conc	
				advice/ attention.	
		P337 + P313		If eye irritation persi	ists: Get medical
				advice/ attention.	
		Storage:			
		P410 + P412		Protect from sunligh	nt. Do not expose
				to temperatures exc	
				122 °F.	Ť
		Disposal:			
		P501		Dispose of contents	s/ container to an
				an annual waste die	

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : inorganic metal-nonmetal compound, organic solvent,

aldehyde/ketone, silicatic material, hydrocarbon, aliphatic

approved waste disposal plant.

Hazardous components

Chemical Name	CAS-No.	Concentration (%)
ethanol	64-17-5	>= 30 - < 50
propane	74-98-6	>= 20 - < 30



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

LA LMM-14 Aerosol		GSLA_LMM-14 Blac	k Aerosol Spray Can
Product specification	RS_FP_603542	Revision Date	04/19/2018
Version	1.13	Print Date	06/18/2018
Material number	1407083	Page	Page 3 of 17

Trade Secret Molybdenum Compound	Not Assigned	>= 10 - < 20
acetone	67-64-1	>= 5 - < 10
quartz	14808-60-7	>= 1 - < 5
Trade Secret Mixed Metal Oxide	Not Assigned	>= 1 - < 5
Trade Secret Silicated compound	Not Assigned	>= 1 - < 5

SECTION 4. FIRST AID MEASURES

General advice : Consult a physician.

If inhaled : Remove to fresh air.

If unconscious place in recovery position and seek medical

advice.

Never give anything by mouth to an unconscious person.

In case of skin contact : Wash off immediately with soap and plenty of water.

If a person feels unwell or symptoms of skin irritation appear,

consult a physician.

In case of eye contact : Rinse immediately with plenty of water and seek medical

advice.

If swallowed : Do NOT induce vomiting.

Rinse immediately with plenty of water and seek medical

advice.

effects, both acute and

delayed

Most important symptoms and : Causes serious eye irritation. May cause respiratory irritation.

May cause drowsiness or dizziness.

May cause cancer.

Suspected of damaging fertility or the unborn child.

Causes damage to organs.

Causes damage to organs through prolonged or repeated

exposure.

SECTION 5. FIREFIGHTING MEASURES

Specific hazards during : Exposure to decomposition products may be a hazard to firefighting health. Do not allow run-off from fire fighting to enter drains or water courses.

Further information: Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment: In the event of fire, wear self-contained breathing apparatus. for firefighters



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

LA LMM-14 AerosolGSLA_LMM-14 Black Aerosol Spray CanProduct specificationRS_FP_603542Revision Date04/19/2018Version1.13Print Date06/18/2018Material number1407083PagePage 4 of 17

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and

: Ensure adequate ventilation.

emergency procedures

Follow safe handling advice and personal protective

equipment recommendations.

Environmental precautions

: Do not flush into surface water or sanitary sewer system.

Prevent product from entering drains.

Methods and materials for

containment and cleaning up

: Sweep up and shovel into suitable containers for disposal.

Clean contaminated floors and objects thoroughly while

observing environmental regulations.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire: Keep away from heat and sources of ignition.

and explosion

Advice on safe handling : Do not get in eyes or mouth or on skin.

For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Do not use in areas without adequate ventilation. Keep

away from heat and sources of ignition.

Conditions for safe storage : Keep in a dry, cool and well-ventilated place.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethanol	64-17-5	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,900 mg/m3	OSHA P0
		STEL	1,000 ppm	ACGIH
propane	74-98-6	TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm	OSHA P0



According to OSHA Hazard Communication Standard 29CFR 1910.1200

(HCS 2012)

LA LMM-14 Aerosol		GSLA_LMM-14 Blac	GSLA_LMM-14 Black Aerosol Spray Can		
Product specification	RS_FP_603542	Revision Date	04/19/2018		
Version	1.13	Print Date	06/18/2018		
Material number	1407083	Page	Page 5 of 17		

			1,800 mg/m3	
Trade Secret Molybdenum Compound	Not Assigned	TWA	5 mg/m3 (Molybdenum)	OSHA Z-1
		TWA (Respirable fraction)	0.5 mg/m3 (Molybdenum)	ACGIH
		TWA	5 mg/m3 (Molybdenum)	OSHA P0
acetone	67-64-1	TWA	500 ppm	ACGIH
		STEL	750 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0
quartz	14808-60-7	TWA (total dust)	30 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable fraction)	0.025 mg/m3 (Silica)	ACGIH
		TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL
Trade Secret Mixed Metal Oxide	Not Assigned	TWA	0.015 mg/m3 (Nickel)	NIOSH REL
Trade Secret Silicated compound	Not Assigned	TWA (Respirable fraction)	3 mg/m3	ACGIH
		TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	3 mg/m3	NIOSH REL
		TWA (respirable dust fraction)	3 mg/m3	OSHA P0

Biological occupational exposure limits

Components	CAS-No.	Control	Biological	Sampling	Permissible	Basis	
		parameters	specimen	time	concentration		



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

LA LMM-14 Aerosol		GSLA_LMM-14 Blac	k Aerosol Spray Can
Product specification	RS_FP_603542	Revision Date	04/19/2018
Version	1.13	Print Date	06/18/2018
Material number	1407083	Page	Page 6 of 17

acetone	67-64-1	Acetone	Urine	End of shift (As	50 mg/l	ACGIH BEI
				soon as		
				possible		
				after		
				exposure ceases)		

Engineering measures: Apply technical measures to comply with the occupational exposure limits.

Provide adequate ventilation.

Personal protective equipment

Respiratory protection : When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

Hand protection

Material : Protective gloves

Eye protection : Safety glasses with side-shields

Ensure that eyewash stations and safety showers are close to

the workstation location.

Protective measures : Wear suitable protective equipment.

Avoid contact with skin.

When using do not eat, drink or smoke.

Hygiene measures : Remove contaminated clothing and protective equipment

before entering eating areas.

Wash hands before breaks and immediately after handling the

product.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : aerosol

Colour : black

Odour : characteristic

Odour Threshold : No data available

pH : No data available

Melting point/range : No data available

Boiling point/boiling range : No data available

Flash point : 14 °C



According to OSHA Hazard Communication Standard 29CFR 1910.1200

(HCS 2012)

LA LMM-14 Aerosol		GSLA_LMM-14 Blac	GSLA_LMM-14 Black Aerosol Spray Can		
Product specification	RS_FP_603542	Revision Date	04/19/2018		
Version	1.13	Print Date	06/18/2018		
Material number	1407083	Page	Page 7 of 17		

Evaporation rate : No data available

Burning rate : No data available

Upper explosion limit : 19 %(V)

Lower explosion limit : 2.1 %(V)

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Bulk density : No data available

Solubility(ies)

Water solubility : soluble

Solubility in other solvents : No data available

Partition coefficient:

noctanol/water

: No data available

Auto-ignition temperature : Not determined

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : No data available

Explosive properties : No data available

Oxidizing properties : No data available

Refractive index : No data available

Volatile organic compounds

(VOC) content

: The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR

60.489):

This product contains the following VOC exemptions listed

under the U.S. Clean Air Act Section 450.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No data available

Chemical stability : No data available

Possibility of hazardous

reactions

: No data available



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

LA LMM-14 AerosolGSLA_LMM-14 Black Aerosol Spray CanProduct specificationRS_FP_603542Revision Date04/19/2018Version1.13Print Date06/18/2018Material number1407083PagePage 8 of 17

Conditions to avoid : Extremes of temperature and direct sunlight.

Incompatible materials : No data available

Hazardous decomposition

products

: Stable under normal conditions.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

inhalation (dust/mist/fume) inhalation (vapour)

Skin

Eye contact Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Components:

ethanol:

Acute oral toxicity : LD50 Oral (Rat): 10,470 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 15,800 mg/kg

propane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h
Test atmosphere: gas

Trade Secret Molybdenum Compound:

Acute oral toxicity : LD50 (Rat, male and female): 4,461 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Acute inhalation toxicity : LC50 (Rat, male and female): > 5,840 mg/m3

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403 Target Organs: Mucous membranes

GLP: yes

Assessment: The substance or mixture has no acute

inhalation toxicity

Remarks: No adverse effect has been observed in acute

toxicity tests.



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

LA LMM-14 AerosolGSLA_LMM-14 Black Aerosol Spray CanProduct specificationRS_FP_603542Revision Date04/19/2018Version1.13Print Date06/18/2018Material number1407083PagePage 9 of 17

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg

Method: OECD Test Guideline 402

GLP: yes

Assessment: The substance or mixture has no acute dermal

toxicity

acetone:

Acute oral toxicity : LD50 Oral (Rat): 5,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): 50,100 mg/m3

Exposure time: 8 h

Acute dermal toxicity : LD50 (Rabbit): > 15,700 mg/kg

quartz:

Acute oral toxicity : LD50 Oral (Rat): 500 mg/kg

Assessment: The substance or mixture has no acute oral

toxicity

Trade Secret Mixed Metal Oxide:

Acute oral toxicity : LD50 (Rat, male and female): > 2,000 mg/kg

Assessment: The substance or mixture has no acute oral toxicity

Remarks: No significant adverse effects were reported

Skin corrosion/irritation

Not classified based on available information.

Components:

ethanol:

Species: Rabbit Exposure time: 24 h

Method: OECD Test Guideline 404

Result: No skin irritation

Trade Secret Molybdenum Compound:

Species: Rabbit Exposure time: 4 h

Assessment: No skin irritation Method: OECD Test Guideline 404

Result: No skin irritation

GLP: yes

acetone:

Assessment: Irritating to skin. Result: Irritating to skin.

Trade Secret Mixed Metal Oxide:

Species: Rabbit Exposure time: 4 h

Method: OECD Test Guideline 404

Result: No skin irritation



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

LA LMM-14 Aerosol		GSLA_LMM-14 Blac	k Aerosol Spray Can
Product specification	RS_FP_603542	Revision Date	04/19/2018
Version	1.13	Print Date	06/18/2018
Material number	1407083	Page	Page 10 of 17

GLP: no

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

ethanol:

Species: Rabbit

Result: Moderate eye irritation Method: OECD Test Guideline 405

Trade Secret Molybdenum Compound:

Species: Rabbit

Result: Irritating to eyes.
Assessment: Irritating to eyes.

acetone:

Result: Irritating to eyes. Assessment: Irritating to eyes.

Trade Secret Mixed Metal Oxide:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

GLP: no

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer.

IARC Group 1: Carcinogenic to humans

quartz 14808-60-7

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP Known to be human carcinogen

quartz 14808-60-7

Reproductive toxicity

Suspected of damaging fertility or the unborn child.



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

LA LMM-14 Aerosol GSLA LMM-14 Black Aerosol Spray Can Product specification RS_FP_603542 **Revision Date** 04/19/2018 Version 1.13 Print Date 06/18/2018 Material number 1407083 Page 11 of 17 Page

STOT Specific Target Organ Toxicity - single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness. Causes damage to organs.

Components:

Trade Secret Molybdenum Compound:

Assessment: May cause respiratory irritation.

STOT Specific Target Organ Toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Components:

ethanol:

Toxicity to daphnia and other : LC50 (Daphnia (water flea)): 9,268 mg/l

aquatic invertebrates Exposure time: 48 h

Trade Secret Molybdenum Compound:

Toxicity to fish : (Oncorhynchus mykiss (rainbow trout)): 100 mg/l

Method: OECD Test Guideline 203

Remarks: No toxicity at the limit of solubility

(Pimephales promelas (fathead minnow)): 370 mg/l

Exposure time: 96 h

Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other

: (Daphnia magna (Water flea)): 100 mg/l

aquatic invertebrates Exposure time: 24 h

Method: OECD Test Guideline 202

Remarks: No toxicity at the limit of solubility

(Daphnia magna (Water flea)): 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: No toxicity at the limit of solubility

acetone:



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

LA LMM-14 Aerosol		GSLA_LMM-14 Blac	GSLA_LMM-14 Black Aerosol Spray Can		
Product specification	RS_FP_603542	Revision Date	04/19/2018		
Version	1.13	Print Date	06/18/2018		
Material number	1407083	Page	Page 12 of 17		

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.74 mg/l

Exposure time: 96 h

LC50 (Pimephales promelas (fathead minnow)): 6,210 - 8,120

mg/l

Exposure time: 96 h Test Type: static test

LC50 (Lepomis macrochirus (Bluegill sunfish)): 8,300 mg/l

Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 10,294 mg/l aquatic invertebrates

Exposure time: 48 h

Trade Secret Mixed Metal Oxide:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l

Exposure time: 96 h Test Type: static test

GLP: yes

Remarks: No toxicity at the limit of solubility

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Components:

ethanol:

Biodegradability : Remarks: No data available

propane:

Biodegradability : Remarks: No data available

Trade Secret Molybdenum Compound:

Biodegradability : Remarks: No data available

acetone:

Biodegradability : Remarks: No data available

quartz:

Biodegradability : Remarks: No data available

Trade Secret Mixed Metal Oxide:

Biodegradability : Remarks: No data available

Trade Secret Silicated compound:

Biodegradability : Remarks: No data available



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

LA LMM-14 AerosolGSLA_LMM-14 Black Aerosol Spray CanProduct specificationRS_FP_603542Revision Date04/19/2018Version1.13Print Date06/18/2018Material number1407083PagePage 13 of 17

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Components:

ethanol:

Bioaccumulation : Remarks: No data available

Partition coefficient: : log Pow: -0.349 (24 °C)

noctanol/water

propane:

Bioaccumulation : Remarks: No data available

Partition coefficient: : Remarks: No data available

noctanol/water

Trade Secret Molybdenum Compound:

Bioaccumulation : Remarks: No data available

acetone:

Bioaccumulation : Remarks: No data available

Partition coefficient: : log Pow: -0.24

noctanol/water

quartz:

Bioaccumulation : Remarks: No data available

Trade Secret Mixed Metal Oxide:

Bioaccumulation : Remarks: No data available

Trade Secret Silicated compound:

Bioaccumulation : Remarks: No data available

Mobility in soil

Product:

Distribution among: Remarks: No data available environmental compartments

Components:

ethanol:

Distribution among: Remarks: No data available environmental compartments

propane:

Distribution among: Remarks: No data available environmental compartments



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

LA LMM-14 AerosolGSLA_LMM-14 Black Aerosol Spray CanProduct specificationRS_FP_603542Revision Date04/19/2018Version1.13Print Date06/18/2018Material number1407083PagePage 14 of 17

Trade Secret Molybdenum Compound:

Distribution among: Remarks: No data available environmental compartments

acetone:

Distribution among: Remarks: No data available environmental compartments

quartz:

Distribution among: Remarks: No data available environmental compartments

Trade Secret Mixed Metal Oxide:

Distribution among: Remarks: No data available environmental compartments

Trade Secret Silicated compound:

Distribution among : Remarks: No data available

environmental compartments

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82

Protection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air

Act Section 602 (40 CFR 82, Subpt. A, App.A +

B).

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of wastes in an approved waste disposal facility.

SECTION 14. TRANSPORT INFORMATION

IATA-DGR

UN number : UN 1950

Proper shipping name : Aerosols, flammable

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 Packing instruction (cargo : 203

aircraft)



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

LA LMM-14 Aerosol GSLA LMM-14 Black Aerosol Spray Can 04/19/2018 Product specification RS_FP_603542 **Revision Date** Version 1.13 Print Date 06/18/2018 Material number 1407083 Page Page 15 of 17

: 203

Packing instruction (passenger aircraft)

IMDG-Code

UN number : UN 1950 Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : UN 1950 Proper shipping name : AEROSOLS

Class

Packing group : Not assigned by regulation

Labels : 2.1 **ERG Code** : 126 Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

TSCA list : TSCA_12b - Not relevant

TSCA list : TSCA 5a - Not relevant

EPCRA - Emergency Planning and Community Right-to-Know Act CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
acetone	67-64-1	5000	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard

> Chronic Health Hazard Acute Health Hazard



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

LA LMM-14 Aerosol		GSLA_LMM-14 Blac	GSLA_LMM-14 Black Aerosol Spray Can		
Product specification	RS_FP_603542	Revision Date	04/19/2018		
Version	1.13	Print Date	06/18/2018		
Material number	1407083	Page	Page 16 of 17		

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 : This product contains components that are reportable under

the regulation.

Molybdenum trioxide

Nickel Compounds

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product contains components that are reportable under the regulation.

This product contains components that are reportable under the regulation.

This product contains components that are reportable under the regulation.

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product contains components that are reportable under the regulation.

Massachusetts Right To Know

This product contains components that are reportable under

the regulation.

Pennsylvania Right To Know

This product contains components that are reportable under

the regulation.

New Jersey Right To Know

This product contains components that are reportable under

the regulation.

California Prop 65 WARNING! This product contains a chemical known to the

State of California to cause cancer.

The components of this product are reported in the following inventories:

EINECS (European Union) : On the inventory, or in compliance with the inventory

SWISS (Switzerland) : On the inventory, or in compliance with the inventory

TSCA (United States) : On TSCA Inventory

DSL/NDSL (Canada) : All components of this product are on the Canadian DSL.

AICS (Australia) : On the inventory, or in compliance with the inventory

NZioC (New Zealand) : On the inventory, or in compliance with the inventory



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

LA LMM-14 AerosolGSLA_LMM-14 Black Aerosol Spray CanProduct specificationRS_FP_603542Revision Date04/19/2018Version1.13Print Date06/18/2018Material number1407083PagePage 17 of 17

ENCS (Japan) : On the inventory, or in compliance with the inventory

ISHL (Japan) : Not in compliance with the inventory

KECI (Korea) : On the inventory, or in compliance with the inventory

PICCS (Philippines) : On the inventory, or in compliance with the inventory

IECSC (China) : On the inventory, or in compliance with the inventory

TCSI (Taiwan) : On the inventory, or in compliance with the inventory

CICR (Turkey) : Not in compliance with the inventory

INSQ (Mexico) : Not in compliance with the inventory

SECTION 16. OTHER INFORMATION

Revision Date : 04/19/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN